

TYPE APPROVAL CERTIFICATE

DNV·GL

This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the DNV GL Type Approval System.

Certificate No. **26 702 - 05 HH**

Company **Barksdale GmbH**
Dorn-Assenheimer Str. 27
61203 Reichelsheim, GERMANY

Product Description **Temperature switch**

Type **MT1H, ML1H, T2H, L2H**

Environmental Category **D, EMC1**

Technical Data /
Range of Application **MT1H, ML1H : single switch type**
T2H, L2H : dual switch type
Temperature sensor: liquid filled local sensor or remote sensor with capillary
(with or without thermowell)
Measuring ranges: -45 ... 66°C to +160...+316°C (capillary)
-45 ... 24°C to +149...+232°C (local sensor)
Sensor and capillary: stainless steel
Electrical connection: c/o contact, microswitch type H, M, L, S, J, K, GH or GM

Contact rating: 125V AC to 250V AC, 10A; 480V AC, 3A (type: H, M, S, GH, GM)
6V DC to 24V DC, 0.5A (type: H, M, S, GH, GM)
250V AC, 15A (type: J, K)
250V AC, 22A (type L)

Ex-proof protection according to the Certificate No. ISSeP08ATEX016X1
Degree of protection: IP65

Test Standard **GL Guidelines for the Performance of Type Approvals, Chapter 2 – Test Requirements for Electrical / Electronic Equipment and Systems (VI-7-2), Edition 2012**

Documents **Test Reports: BFSV No. 5704/05 and BFSV No. 5769/05**
Certificate No. ISSeP08ATEX016X1
Data sheets: 05/04 KTM-EN 03/02, 05/03 KTM-EN 03/01, 05/03 KTM-EN 03/1,
Construction drawings

Remarks **Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL**

Valid until **2020-10-20**

Page **1 of 1**

File No. **I.D.02**

Hamburg, 2015-10-21

Type Approval Symbol



DNV GL

i.v. Le
Dr. Duy Nam Le

i.D. Lesniewski
Dariusz Lesniewski